

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A signal processing circuit for transmitting data as packet data to a serial interface bus in a predetermined time cycle, comprising:

a cipher processing circuit for enciphering the data to be transmitted by one of a number of predetermined cipher modes, in which one of said predetermined cipher modes is a copy once prohibition mode wherein the data can not be reproduced more than once; and

B<sup>1</sup>  
a transmission circuit for adding ~~the enciphering information~~ representative of the cipher mode to the data enciphered in the cipher processing circuit, and transmitting the result-enciphered data and the enciphering information to the serial interface bus, and for determining whether confirming the continuity of the cipher mode by and the enciphering information correspond when transmitting a plurality of packets, and when the cipher mode and enciphering information are determined not to correspond transmitting the data enciphered by a different cipher mode to the serial interface bus as packet data in ~~the other~~ another cycle ~~when a discontinuity is confirmed~~.

2. (Original) A signal processing circuit as set forth in claim 1, wherein the transmission circuit sets the enciphering information in a predetermined region of a header of the packet.

3. (Currently Amended) A signal processing circuit for transmitting data as packet data to a serial interface bus in a predetermined time cycle, comprising:

a holding means in which information of at least one of a number of cipher modes is set, wherein one of said cipher modes is a copy once prohibition mode wherein the data can not be reproduced more than once;

a control means for specifying a cipher mode for to encipher enciphering the data  
for transmission data;

a cipher processing circuit including a cipher mode selection circuit for ~~selecting~~  
accessing the cipher mode information specified by the control means from the holding means;  
and

a cipher engine circuit for enciphering the data to be transmitted in the cipher  
mode selected in the cipher mode selection circuit and outputting the enciphered data;

a transmission circuit for adding ~~the~~ enciphering information representative of the  
cipher mode to the enciphered data in the cipher processing circuit, and ~~transmitting the~~  
enciphered data and enciphering information result to the serial interface bus,; and for  
determining whether the cipher mode confirming the continuity of the cipher mode by and the  
enciphering information correspond ~~when transmitting a plurality of packets, and when the cipher~~  
mode and enciphering information are determined not to correspond transmitting the data  
enciphered by a different cipher mode to the serial interface bus as packet data in another cycle  
when a discontinuity is confirmed.

4. (Original) A signal processing circuit as set forth in claim 3, wherein the  
transmission circuit sets the enciphering information in a predetermined region of a header of the  
packet.

5. (Currently Amended) A signal processing circuit for transmitting data as packet  
data to a serial interface bus in a predetermined time cycle, comprising:

a storing means;

a holding means in which information of at least one of a number of cipher modes  
is set, wherein one of said cipher modes is a copy once prohibition mode wherein the data can  
not be reproduced more than once;

a control means for specifying a cipher mode for enciphering to encipher the  
transmission data;

a cipher processing circuit including a cipher mode selection circuit for accessing  
the selecting cipher mode information specified by the control means from the holding means  
and

a cipher engine circuit for enciphering the data to be transmitted in the cipher mode ~~selected~~ accessed in the cipher mode selection circuit and outputting ~~the~~ enciphered data;

a first transmission circuit for generating time information ~~to output received data on a receiving side to an application side,~~ adding to the time information the enciphering information, and storing the result in the storing means along with the enciphered data; and

a second transmission circuit for reading enciphered data to which has been added time information and enciphering information stored in the storing means, generating packet data in a predetermined format, setting the enciphering information in the packet header, and transmitting the result to the serial interface bus and, when transmitting a plurality of packets, confirming continuity of the cipher mode from the enciphering information, stopping the transmission when the cipher mode and the enciphering information are determined not to correspond ~~confirming a discontinuity~~ even if there is room in a band enabling transmission in the predetermined time cycle, and transmitting the data enciphered by a different cipher mode to the serial interface bus as packet data in a next cycle.

6. (Currently Amended) A signal processing circuit for transmitting and receiving data as enciphered packet data to and from a serial interface bus in a predetermined time cycle, ~~wherein the enciphered packet data is received and output to the application side,~~ comprising:

a cipher processing circuit for enciphering the data to be transmitted by one of a number of a predetermined cipher modes at the time of transmission, wherein one of said predetermined cipher modes is a copy once prohibition mode wherein the data can not be reproduced more than once, and deciphering ~~the~~ received enciphered data based on the enciphering information included in ~~the~~ a received packet data at the time of reception; and

a transmission circuit for adding the enciphering information to the data enciphered ~~data~~ in the cipher processing circuit, transmitting the result to the serial interface bus, confirming the continuity of the cipher mode by the enciphering information when transmitting a plurality of packets, and transmitting the data enciphered by a different cipher mode to the serial interface bus as packet data in another cycle when the cipher mode and the enciphering information are determined not to correspond ~~a discontinuity is confirmed~~.

7. (Original) A signal processing circuit as set forth in claim 6, wherein the transmission circuit sets the enciphering information in a predetermined region of a header of the packet.

8. (Currently Amended) A signal processing circuit for transmitting and receiving data as enciphered packet data to and from a serial interface bus in a predetermined time cycle, ~~wherein the enciphered packet data is received and output to the application side,~~ comprising:

a first storing means;

a second storing means;

a holding means in which information of at least one of a number of cipher modes is set, wherein one of said cipher modes is a copy once prohibition mode wherein the data can not be reproduced more than once;

a control means for specifying a cipher mode ~~for to encipher~~ enciphering the transmission data;

B<sup>1</sup> a first reception circuit for storing time information, enciphered data and the enciphering information ~~from the~~ of received packet data in the first storing means;

a second reception circuit for outputting the enciphering information and the enciphered data stored in the first storing means and indicating a time ~~for to be output~~ outputting the received data ~~to an application side~~ based on the time information;

a cipher processing circuit including a cipher mode detection circuit for detecting a cipher mode used for enciphering data by the enciphering information from the second reception circuit;

a cipher mode selection circuit for ~~selecting~~ accessing cipher mode information specified by the control means at the time of transmission and selecting the cipher mode information detected by the cipher mode detection circuit from the information set in the holding means at the time of reception, ~~and~~;

a cipher engine circuit for enciphering the data to be transmitted in the cipher mode ~~selected~~ accessed in the cipher mode selection circuit ~~and~~, outputting the enciphered data at the time of transmission and deciphering the received data in the cipher mode ~~selected~~ accessed in the cipher mode selection circuit at the time of reception;

a first transmission circuit for generating time information to ~~output received data on a receiving side to an application side,~~ adding to the time information the enciphering information, and storing the result in the second storing means along with the enciphered data; and

B1  
a second transmission circuit for reading enciphered data to which has been added time information and enciphering information stored in the second storing means, generating packet data in a predetermined format, setting the enciphering information in the packet header and transmitting the result to the serial interface bus and, when transmitting a plurality of packets, confirming the continuity of the cipher mode from the enciphering information, stopping the transmission when the cipher mode and the enciphering information are determined not to correspond ~~confirming a discontinuity~~ even if there is room in a band enabling transmission in the predetermined time cycle, and transmitting the data enciphered by a different cipher mode to the serial interface bus as packet data in a next cycle.

---